

04

Cylinder Lubricator - Atlas / Alpha

Cylinder Lubricator - Atlas / Alpha

- Atlas Lubricator
- Alpha Lubricator
- ME Lubricator
- Booster Pump
- Heating Tank

Cylinder Lubricator is a special pump designed to supply lubricating oil to a cylinder liner. It consists of a plunger and barrel. The product is used to increase sealing effect and reduce corrosion or friction between piston ring and cylinder liner.

Atlas Lubricator

Mechanical Lubricators for MAN low speed diesel engines



K90MC



K90, 98MC-C




S46MC-C



L, S 50MC



S60MC-C



S35MC

Alpha / ME Lubricator

Electronical Lubricators for MAN low speed diesel engines



50 - 60MC(MC-C)



70 - 98 MC(MC-C)



Charging Tool



50-98ME/ ME-C

Booster Pump

Booster Pump for MAN low speed diesel engines



Division type



Complete type

Type	Flow Rate	Pump Size	Motor Speed	Motor Size	Motor Voltage	Motor Frequency	Mass
1	0.4m ³ /h	4cm ³	1,700RPM	2.2KW	440V	60Hz	275kg
2	0.8m ³ /h	8cm ³	1,700RPM	2.2KW	440V	60Hz	275kg
3	1.3m ³ /h	14cm ³	1,700RPM	3.0KW	440V	60Hz	275kg
4	0.4m ³ /h	5.5cm ³	1,410RPM	2.2KW	380V	50Hz	275kg
5	0.8m ³ /h	9.9cm ³	1,410RPM	2.2KW	380V	50Hz	275kg
6	1.3m ³ /h	16cm ³	1,410RPM	3.0KW	380V	50Hz	275kg

Heating Tank

Heating Tank for MAN low speed diesel engines



Type	Flow Rate	Pump Size	Motor Speed	Motor Size	Motor Voltage	Motor Frequency	Mass
1	105 gal/hr	0.25in ³	1,700RPM	2.2KW	440V	60Hz	605lb
2	211 gal/hr	0.49in ³	1,700RPM	2.2KW	440V	60Hz	605lb
3	343 gal/hr	0.85in ³	1,700RPM	3.0KW	440V	60Hz	605lb
4	105 gal/hr	0.34in ³	1,410RPM	2.2KW	380V	50Hz	605lb
5	211 gal/hr	0.60in ³	1,410RPM	2.2KW	380V	50Hz	605lb
6	343 gal/hr	0.98in ³	1,410RPM	3.0KW	380V	50Hz	605lb