

## ■ LED Lamp

### [Features and Benefits]

Rated input voltage 100-240V

Substitutable for E26 lamp or E26 fluorescent lamp for example "EFA15" and "EFD15".

Suitable for downlight equipment a lamp installed horizontally.

Beam angle up to 200°

Long lifespan up to 15000hours(Rated life is average value, not for guarantee)

Able to be used for a sealed equipment and an equipment for outdoor,  
except a bottom opening equipment and an outdoor wired equipment.

### [Lighting instruments]

Downlight, Stand, Pendant, Bracket, etc...



- ※1 In case of being used outdoor, this lamp must be used with an equipment have a moisture and a rain proof except a bottom opening equipment.
- ※2 This lamp must be used in temperature in -20°C to 40°C, and must be avoided from direct sunlight.
- ※3 This lamp must be used with a concealed wired equipment.

If you don't compliance to the above, that might cause life-span of this lamp short and unexpected bug as a result.

	Model No.	Packing unit	Color temperature	Base	External size (mm)		Power consumption (W)	Lamp voltage (V)	Luminous Efficacy (lm/W)	Luminous flux (lm)	Dimmable	Normal lamp-lifetime (h)
					Overall length (L)	Diameter (D)						
Equivalent of 50W Incandescent lamp	LDT7D-VS/E26	10	Cool Daylight (6500K)	E26	114	41.0	7	100-240	107	750	No	15000
	LDT7L-VS/E26	10	Lamp color (2700K)	E26	114	41.0	7	100-240	100	700	No	15000
Equivalent of 70W Incandescent lamp	LDT9D-VS/E26	10	Cool Daylight (6500K)	E26	114	41.0	9	100-240	106	950	No	15000
	LDT9L-VS/E26	10	Lamp color (2700K)	E26	114	41.0	9	100-240	100	900	No	15000

- ※Do not use with dimmer,even for full power.
- ※Never modify this lamp.
- ※Never use for DC power supply.
- ※Rated life is average value,not for guarantee.

### [Information]

## OSRAM LEDVANCE

General Agency

KOYO Denki.co.ltd

3-1-18 Hiyoshi-town, Nagata-ward,  
Kobe city, Hyogo prectecture  
653-0039

TEL:078-631-1212 FAX:078-647-5511

<http://www.koyodenki.co.jp>

E-mail:ship@koyodenki.co.jp

Sales Agency